



E		F	
版本号 Version No.	内容 Content	设计 Designer	日期 Date
△1			
△2			
△3			
△4			
最大工作压力 Maximum Working Pressure		20	Bar
工作温度 working Temp		-20~150	°C
最大工作流量 Maxum Working Flow		15.07	L/min
机械寿命(插拔次数) Mechanical Life(Plugging Time)		>1000	次 time
密封方式 Sealing Mode		双向 double	
名称 Name		参数 Parameter	单位 Unit
主体材质 Material of Main Body		316L	
O型圈材质 Material of O-ring		EPDM	
介质 Medium		冷却液、水-乙二醇 coolant, water-ethylene glycol	
名称 Name		参数 Parameter	

**注意事项:**

- 禁止超过最大工作压力、温度、流量使用;
- 禁止将产品作为铰链接头使用;
- 禁止将产品与本公司以外的产品互换使用;
- 禁止私自拆卸产品或拆卸后更换零部件后再使用;
- 禁止应用在可用介质以外的流体中;
- 安装使用需考虑防松措施;
- 工作介质须保证流体洁净度, 推荐优于GJB420B-9级;
- 使用前, 确保流体连接器洁净无污染;
- 安装或使用过程中有漏液或其他任何问题, 请联系我司。

**Matters needing attention**

- Do not use over the maximum working pressure and the maximum temperature and the maximum flow;
- Do not use the product as a hinge joint;
- It is forbidden to use the product interchangeably with other products outside the company;
- It is forbidden to disassemble the product without permission or replace the parts after disassembly before use;
- Do not use in fluids other than available media;
- Loose-proof measures shall be considered for installation and use;
- The working medium shall ensure the fluid cleanliness, which is recommended to be better than GJB420B-9;
- Ensure that the fluid connector is clean and pollution-free before use;
- Please contact us for any leakage or other problems during installation or use.

备注 Note	颜色(色号) Color (Color Number)	<b>BEISIT</b>	X	±0,5	产品型号 Item NO.	BST-PP-08	产品名称 Item Name	流体连接器 Fluid Connector	材料 Material	产品物料号 Product Material No.	倍仕得货号 Beisit No.
			X.X	±0,3	制图 Drawer	毛天良/Tianliang Mao	日期 Date	2022/8/17	单位 Unit	MM	110403000006
			X.XX	±0,08	设计 Designer	毛天良/Tianliang Mao	日期 Date	2022/8/17	比例 Scale	1104030000014	BST-PP-8SSSE2G38
			X.XXX	±0,05	审核 Approved by	李小强/Roy Li	日期 Date	2022/8/17	视图 View		